

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

### Section 1. Identification of the substance or the mixture and of the supplier

#### 1.1 Product Identifier

**Product identifier:** Energy LUX 0078(Contains:Linalool, alpha-iso-Methylionone, d-Limonene)

**Other identifiers:** None

#### 1.2 Relevant identified uses of the substance of mixture and uses advised against

**Product uses:** Fragrances

#### 1.3 Details of the supplier of the safety data sheet

**Company name:** Luxaroma Pty Ltd

**Company address:** 27 Union Circuit  
Yatala  
QLD 4207  
Australia

**Contact:** Regulatory Affairs

**E-Mail address:** info@luxaroma.com.au

**Company phone:** 1300 888 360

#### 1.4 Emergency telephone number

**Emergency phone:** 1300 888 360

### Section 2. Hazards identification

#### 2.1 Classification of the substance or mixture

**Class and category of danger:** Flammable Liquid, Hazard Category 4  
Skin Corrosion / Irritation Category 2  
Sensitization - Skin Category 1  
Aspiration Hazard Category 1  
Hazardous to the Aquatic Environment - Acute Hazard Category 1  
Hazardous to the Aquatic Environment - Long-term Hazard Category 1  
H227, Combustible liquid.  
H304, May be fatal if swallowed and enters airways.  
H315, Causes skin irritation.  
H317, May cause an allergic skin reaction.  
H410, Very toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Signal word:** Danger

**Hazard statements:** H227, Combustible liquid.  
H304, May be fatal if swallowed and enters airways.  
H315, Causes skin irritation.  
H317, May cause an allergic skin reaction.

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

H410, Very toxic to aquatic life with long lasting effects.

**Precautionary statements:**

P210, Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P261, Avoid breathing vapour or dust.

P264, Wash hands and other contacted skin thoroughly after handling.

P272, Contaminated work clothing should not be allowed out of the workplace.

P273, Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection.

P301/310, IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302/352, IF ON SKIN: Wash with plenty of soap and water.

P331, Do not induce vomiting.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P362, Take off contaminated clothing and wash before reuse.

P370/378, In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

P391, Collect spillage.

P403/235, Store in a well-ventilated place. Keep cool.

P405, Store locked up.

P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

**Pictograms:**



**2.3 Other hazards**

**Other hazards:** None

### Section 3. Composition / information on ingredients

**3.2 Mixtures**

**Contains:**

Name	CAS	%	GHS Classification
d-Limonene	5989-27-5	20-<50%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315-H317-H410
Benzyl benzoate	120-51-4	20-<50%	Acute Tox. 4-Acute Tox. 5-Aquatic Acute 1-Aquatic Chronic 2;H302-H313-H400-H411
Methyl ester of rosin (partially hydrogenated)	8050-15-5	20-<50%	Aquatic Acute 3-Aquatic Chronic 3;H412
559-NL Raspberry ketone	5471-51-2	1-<5%	Aquatic Acute 3;H402
Linalool	78-70-6	1-<5%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3;H227-H303-H315-H317-H319-H402

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

Nonanal	124-19-6	1-<5%	Flam. Liq. 4-Skin Irrit. 3-Aquatic Acute 2-Aquatic Chronic 3;H227-H316-H401-H412
alpha-iso-Methylionone	127-51-5	1-<5%	Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H316-H317-H411
Decanal	112-31-2	1-<5%	Flam. Liq. 4-Skin Irrit. 3-Eye Irrit. 2A-Aquatic Acute 2-Aquatic Chronic 3;H227-H316-H319-H401-H412
Lauric aldehyde	112-54-9	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B;H315-H317-H319
Citral	5392-40-5	0.1-<1%	Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1-Aquatic Acute 2;H313-H315-H317-H319-H401
Terpineol	8000-41-7	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Aquatic Acute 3;H227-H303-H315-H319-H402
Isoeugenyl methyl ether	93-16-3	0.1-<1%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 3;H303-H317-H402
Myrcene	123-35-3	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Eye Irrit. 2A-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 2;H226-H304-H315-H319-H400-H411
Citronellal	106-23-0	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2;H227-H303-H313-H315-H317-H319-H401
2-Methylundecanal	110-41-8	0.1-<1%	Flam. Liq. 4-Skin Irrit. 2-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H227-H315-H317-H410
(2E)-1-(2,6,6-Trimethyl-1-cyclohexen-1-yl)-2-buten-1-one	23726-91-2	0.1-<1%	Acute Tox. 5-Skin Irrit. 2-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H303-H315-H317-H411
l-Carvone	6485-40-1	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 2;H227-H313-H317-H401
Methyl 2-nonynoate	111-80-8	<0.1%	Acute Tox. 4-Acute Tox. 5-Skin Irrit. 2-Skin Sens. 1A-Aquatic Acute 1-Aquatic Chronic 3;H302-H313-H315-H317-H400-H412

### Substances with workplace exposure limits, not listed above:

Not Applicable

### Section 4. First-aid measures

#### 4.1 Description of first aid measures

**Inhalation:** Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

**Eye exposure:** Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.

**Skin exposure:** IF ON SKIN: Wash with plenty of soap and water.

**Ingestion:** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

### Section 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

#### 5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

#### 5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

### Section 6. Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

#### 6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

#### 6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

#### 6.4 Reference to other sections:

Also refer to sections 8 and 13.

### Section 7. Handling and storage

#### 7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation. Do not eat, drink or smoke when using this product.

#### 7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

### Section 8. Exposure controls/personal protection

#### 8.1 Control parameters

**Workplace exposure limits:** Not Applicable

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

### 8.2 Exposure Controls

#### Eye / Skin Protection

Wear protective gloves/eye protection/face protection

#### Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

### Section 9. Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Clear Orange
<b>Odour:</b>	Not determined
<b>Odour threshold:</b>	Not determined
<b>pH:</b>	Not determined
<b>Melting point / freezing point:</b>	Not determined
<b>Initial boiling point / range:</b>	Not determined
<b>Flash point:</b>	> 70 °C
<b>Evaporation rate:</b>	Not determined
<b>Flammability (solid, gas):</b>	Not determined
<b>Upper/lower flammability or explosive limits:</b>	Product does not present an explosion hazard
<b>Vapour pressure:</b>	Not determined
<b>Vapour density:</b>	Not determined
<b>Relative density:</b>	Not determined
<b>Solubility(ies):</b>	Not determined
<b>Partition coefficient: n-octanol/water:</b>	Not determined
<b>Auto-ignition temperature:</b>	Not determined
<b>Decomposition temperature:</b>	Not determined
<b>Viscosity:</b>	Not determined
<b>Explosive properties:</b>	Not expected
<b>Oxidising properties:</b>	Not expected

**9.2 Other information:** None available

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078  
**Version:** 2

### Section 10. Stability and reactivity

**10.1 Reactivity:**

Presents no significant reactivity hazard, by itself or in contact with water.

**10.2 Chemical stability:**

Good stability under normal storage conditions.

**10.3 Possibility of hazardous reactions:**

Not expected under normal conditions of use.

**10.4 Conditions to avoid:**

Avoid extreme heat.

**10.5 Incompatible materials:**

Avoid contact with strong acids, alkalis or oxidising agents.

**10.6 Hazardous decomposition products:**

Not expected.

### Section 11. Toxicological information

**11.1 Information on toxicological effects**

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

<b>Acute Toxicity:</b>	Based on available data the classification criteria are not met.
Acute Toxicity Oral	>5000
Acute Toxicity Dermal	>5000
Acute Toxicity Inhalation	Not Available
<b>Skin corrosion/irritation:</b>	Skin Corrosion / Irritation Category 2
<b>Serious eye damage/irritation:</b>	Based on available data the classification criteria are not met.
<b>Respiratory or skin sensitisation:</b>	Sensitization - Skin Category 1
<b>Germ cell mutagenicity:</b>	Based on available data the classification criteria are not met.
<b>Carcinogenicity:</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity:</b>	Based on available data the classification criteria are not met.
<b>STOT-single exposure:</b>	Based on available data the classification criteria are not met.
<b>STOT-repeated exposure:</b>	Based on available data the classification criteria are not met.
<b>Aspiration hazard:</b>	Aspiration Hazard Category 1

**Information about hazardous ingredients in the mixture**

Ingredient	CAS	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
Benzyl benzoate	120-51-4	1500	4000	Not available	Not available
Linalool	78-70-6	2790	Not available	Not available	Not available

Refer to Sections 2 and 3 for additional information.

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

### Section 12. Ecological information

**12.1 Toxicity:**

Very toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability:** Not available

**12.3 Bioaccumulative potential:** Not available

**12.4 Mobility in soil:** Not available

**12.5 Other adverse effects:** Not available

### Section 13. Disposal considerations

**13.1 Waste treatment methods:**

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class(es):	Sub Risk:	14.4 Packing Group:
<b>UN Model Regulations</b>	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (d-Limonene, Benzyl benzoate)	9	-	III
<b>IMDG</b>	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (d-Limonene, Benzyl benzoate) MARINE POLLUTANT	9	-	III
<b>ADR,RID,ADN</b>	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (d-Limonene, Benzyl benzoate)	9	-	III
<b>ICAO TI</b>	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (d-Limonene, Benzyl benzoate)	9	-	III

**14.5 Environmental hazards:** This is classified as an environmentally hazardous substance under the UN Model Regulations. This is classified as a Marine Pollutant under the IMDG Code.

**14.6 Special precautions for user:** None additional

**14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:**

Not applicable

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

### Section 15. Regulatory information

None additional

### Section 16. Other information

**Concentration % Limits:**

EH A1=43.33% EH A2=4.29% EH A3=0.42634869% EH C1=85.65% EH C2=7.76% EH C3=0.76919172% EH C4=28.15% SCI 2=31.46% SCI 3=2.84% SS 1=3.44% AH 1=34.44%

**Total Fractional Values:**

EH A1=2.31 EH A2=23.33 EH A3=234.55 EH C1=1.17 EH C2=12.88 EH C3=130.01 EH C4=3.55 SCI 2=3.18 SCI 3=35.22 SS 1=29.04 AH 1=2.90

**Key to revisions:**

Concentration % Limits

GHS Workplace Exposure Limits

Hazardous Ingredients declared in a GHS Product Identifier

Information about hazardous ingredients in the mixture

SECTION 3: Composition/information on ingredients

Total Fractional Values

**Key to abbreviations:**

Abbreviation	Meaning
Acute Tox. 4	Acute Toxicity - Oral Category 4
Acute Tox. 5	Acute Toxicity - Dermal Category 5
Acute Tox. 5	Acute Toxicity - Oral Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.



## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
P210	Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1	Sensitization - Skin Category 1
Skin Sens. 1A	Sensitization - Skin Category 1A

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Energy LUX 0078

**Version:** 2

Skin Sens. 1B	Sensitization - Skin Category 1B
---------------	----------------------------------

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.