

LUXAROMA

Issue date: 15/02/2023

Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: Claret LUX 20236(Contains:241-NL Coumarin, 318-NL Ethyl vanillin, Benzyl benzoate,

Piperonal)

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Fragrances

1.3 Details of the supplier of the safety data sheet

Company name: Luxaroma Pty Ltd Company address: 27 Union Circuit

> Yatala QLD 4207 Australia

Contact: Regulatory Affairs

E-Mail address: info@luxaroma.com.au

1300 888 360 Company phone: 1.4 Emergency telephone number 1300 888 360 **Emergency phone:**

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Class and category of Flammable Liquid, Hazard Category 4 danger:

Acute Toxicity - Oral Category 4

Skin Corrosion / Irritation Category 3 Eye Damage / Irritation Category 2 Sensitization - Skin Category 1

Hazardous to the Aquatic Environment - Acute Hazard Category 1 Hazardous to the Aquatic Environment - Long-term Hazard Category 2

H227, Combustible liquid. H302, Harmful if swallowed. H316, Causes mild skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation. H400, Very toxic to aquatic life.

H411, Toxic to aquatic life with long lasting effects.

2.2 Label elements

Signal word: Warning



Issue date: 15/02/2023

Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

Hazard statements: H227, Combustible liquid.

H302, Harmful if swallowed.

H316, Causes mild skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation. H400, Very toxic to aquatic life.

H411, Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210, Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P261, Avoid breathing vapour or dust.

P264, Wash hands and other contacted skin thoroughly after handling.

P270, Do not eat, drink or smoke when using this product.

P272, Contaminated work clothing should not be allowed out of the workplace.

P273, Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection.

P301/312, IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.

P302/352, IF ON SKIN: Wash with plenty of soap and water.

P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P330. Rinse mouth.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P337/313, If eye irritation persists: Get medical advice/attention.

P363, Wash contaminated clothing before reuse.

P370/378, In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

P391, Collect spillage.

P403/235, Store in a well-ventilated place. Keep cool.

P501, Dispose of contents/container to approved disposal site, in accordance with local

regulations.





2.3 Other hazards

Other hazards: None

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:





Issue date: 15/02/2023

Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

Name	CAS	%	GHS Classification		
Benzyl benzoate	120-51-4	50-100%	Acute Tox. 4-Acute Tox. 5-Aquatic Acute 1-Aquatic Chronic 2;H302-H313-H400-H411		
241-NL Coumarin	91-64-5	10-<20%	Acute Tox. 4-Skin Sens. 1B-Aquatic Acute 3;H302-H317-H402		
318-NL Ethyl vanillin	121-32-4	5-<10%	Acute Tox. 5-Eye Irrit. 2B-Aquatic Acute 3;H303-H320-H402		
602-NL Vanillin	121-33-5	5-<10%	Acute Tox. 5-Eye Irrit. 2A-Aquatic Acute 3;H303-H319-H402		
Piperonal	120-57-0	1-<5%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 2;H303- H317-H401		
gamma-Undecalactone	104-67-6	1-<5%	Skin Irrit. 3-Aquatic Acute 3-Aquatic Chronic 3;H316- H412		
gamma-Decalactone	706-14-9	1-<5%	Skin Irrit. 3;H316		
Diacetyl	431-03-8	0.1-<1%	Flam. Liq. 2-Acute Tox. 4-Acute Tox. 3-Skin Irrit. 2-Ey Dam. 1-Skin Sens. 1-STOT RE 2-Aquatic Acute 3; H225-H302-H315-H317-H318-H331-H373-H402		
486-NL Musk ketone	81-14-1	0.1-<1%	Carc. 2-Aquatic Acute 1-Aquatic Chronic 1;H351-H410		
alpha-iso-Methylionone	127-51-5	0.1-<1%	Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H316-H317-H411		
Isoamyl alcohol	123-51-3	0.1-<1%	Flam. Liq. 3-Acute Tox. 5-Acute Tox. 5-Skin Irrit. 2-Eye Dam. 1-STOT SE 3;H226-H303-H313-H315-H318-H335		
Acetyl cedrene	32388-55-9	0.1-<1%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H303-H317-H410		
d-Limonene	5989-27-5	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1- Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315- H317-H410		
Citral	5392-40-5	0.1-<1%	Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1- Aquatic Acute 2;H313-H315-H317-H319-H401		
Eugenol	97-53-0	0.1-<1%	Acute Tox. 5-Skin Irrit. 3-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2;H303-H316-H317-H319-H401		

Substances with workplace exposure limits, not listed above:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Skin exposure: IF ON SKIN: Wash with plenty of soap and water.

Ingestion: IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

Causes mild skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed



LUXAROMA

Issue date: 15/02/2023

Page 4 (10)

Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

None expected, see Section 4.1 for further information.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable



Page 5 (10)

Issue date: 15/02/2023 Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

9.2 Other information:

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Odour:

Not determined

Odour threshold:

PH:

Not determined

Flash point: > 65 °C

Evaporation rate: Not determined Flammability (solid, gas): Not determined

Upper/lower flammability or explosive limits: Product does not present an explosion hazard

Vapour pressure: Not determined Vapour density: Not determined Not determined Relative density: Solubility(ies): Not determined Partition coefficient: n-octanol/water: Not determined **Auto-ignition temperature:** Not determined **Decomposition temperature:** Not determined Viscosity: Not determined **Explosive properties:** Not expected Oxidising properties: Not expected

None available



Issue date: 15/02/2023

Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Acute Toxicity: Acute Toxicity - Oral Category 4

Acute Toxicity Oral 1599
Acute Toxicity Dermal >5000

Acute Toxicity Inhalation Not Available

Skin corrosion/irritation:Skin Corrosion / Irritation Category 3Serious eye damage/irritation:Eye Damage / Irritation Category 2Respiratory or skin sensitisation:Sensitization - Skin Category 1

Germ cell mutagenicity:

Based on available data the classification criteria are not met.

Carcinogenicity:

Based on available data the classification criteria are not met.

Reproductive toxicity:

Based on available data the classification criteria are not met.

STOT-single exposure:

Based on available data the classification criteria are not met.

STOT-repeated exposure:

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Ingredient	CAS	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
241-NL Coumarin	91-64-5	500	Not available	Not available	Not available
318-NL Ethyl vanillin	121-32-4	3000	Not available	Not available	Not available
602-NL Vanillin	121-33-5	3500	Not available	Not available	Not available



Page 7 (10)

Issue date: 15/02/2023 Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

Benzyl benzoate	120-51-4	1500	4000	Not available	Not available
Diacetyl	431-03-8	1580	Not available	3	Vapour
Piperonal	120-57-0	2700	Not available	Not available	Not available

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class(es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, 486-NL Musk ketone)	9	-	III
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, 486-NL Musk ketone) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, 486-NL Musk ketone)	9	-	III
ICAO TI	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate, 486-NL Musk ketone)	9	-	III

Page 8 (10)



Issue date: 15/02/2023

Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

14.5 Environmental hazards: This is classified as an environmentally hazardous substance under the UN

Model Regulations. This is classified as a Marine Pollutant under the IMDG

Code.

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

None additional

Section 16. Other information

Concentration % Limits: EH A1=44.29% EH A2=4.42% EH A3=0.43981779% EH C2=39.06% EH

C3=3.90% EH C4=43.30% SCI 3=57.15% EDI 2A=43.80% SS 1=9.41%

Total Fractional Values: EH A1=2.26 EH A2=22.64 EH A3=227.37 EH C2=2.56 EH C3=25.66 EH

C4=2.31 SCI 3=1.75 EDI 2A=2.28 SS 1=10.63

Key to revisions:

Not applicable

Key to abbreviations:

Abbreviation	Meaning
Acute Tox. 3	Acute Toxicity - Inhalation Category 3
Acute Tox. 4	Acute Toxicity - Oral Category 4
Acute Tox. 5	Acute Toxicity - Dermal Category 5
Acute Tox. 5	Acute Toxicity - Oral Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Liq. 2	Flammable Liquid, Hazard Category 2
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.



Issue date: 15/02/2023 Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer (exposure route).
H373	May cause damage to organs (organs) through prolonged or repeated exposure (exposure route).
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe vapour or dust.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P281	Use personal protective equipment as required.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to



Page 10 (10)

Issue date: 15/02/2023 Version: 1 (15/02/2023)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: Claret LUX 20236

Version: 1

P308/313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/233/235	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
STOT RE 2	Specific Target Organ Toxicity (Repeated Exposure) Category 2
STOT SE 3	Specific Target Organ Toxicity (Single Exposure) Category 3
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1	Sensitization - Skin Category 1
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.